

7020-series

Tank shower, open side cabin with over head tank

Tank shower with insulated tank and frame made of stainless steel. The stainless steel tank is corrosion resistant and guarantees a flush time of +15 minutes. It is fitted with pictogram signs and green/white stripes for the visibility of the tank shower. Shower head made of powder-coated stainless steel (SS316), stay-open ball valve, operated by a pull handle.

Available with explosion-proof construction for EX-Zone 1 & 2. Manufactured in accordance to ANSI Norm Z358.1-2004 and SS-EN 15154-1 & 2:2006.

TECHNICAL DATA

Flow rate emergency shower: 76 L/min

Water inlet: 1" male

Water overflow: Pipe thread external 1"

Water level indicator: Visual pointing outside tank

Weight: approx. 370 kg

Options: Eyewash, step-on footgrid, panic-bar, alarm, heating element, cooler, flashing light, thermometer, anti-bacterial fluid, back/side panels, catchment and undertank lightning.

TECHNICAL INFORMATION

Model no.: 7020	Width:	1344 mm (measured at top)
Tank size: 1200L	Height:	3621 mm
	Depth:	1226 mm

Model no.: 7021	Width:	1344 mm (measured at top)
Tank size: 1400L	Height:	3621 mm
	Depth:	1226 mm

