

8020

Self-draining emergency shower and eye/facewash system

Product information

A free-standing, self-draining emergency shower and eye/facewash system for outdoor/indoor use. The safety station is delivered with galvanized steel pipes, green/white stripe, spray heads made of ABS-plastic and shower head in powder-coated stainless steel. Facewash 3864, each individual spray head has built-in flow control and filter.

The product is extra suitable in warm climates

This self-draining emergency shower and eye/facewash prevents hot stagnant water inside the shower.

Designed for minimum flow of 76 l/min at 2.4 bar pressure, the water connection area should be modified according to existing climate conditions. The flow rates are guaranteed only when the pressure in the main pipeline is approximately 2.4-6.5 bar.

Emergency signs are enclosed with each safety station.

Options

- Alarm
- Foot pedal or step-on foot grid
- Stainless steel dustcover
- Flange connection
- Stainless steel

This product is manufactured in accordance to ANSI Norm Z358.1-2009 and EN 15154-1 & 2:2006.



Technical information

Flow rate shower: ca 76 l/min
Flow rate eyewash: ca 28 l/min
Water supply: 1"

Width: 400 mm
Height: 2320 mm
Depth: 790 mm



Visiting address

Metallverksgatan 12
SE-721 30 Västerås

Postal address

Box 404
SE-721 08 Västerås

Tel +46 (0)21-14 92 00
Fax +46 (0)21-14 92 50
www.krusman.com

Krusman
We ensure safety in risky environments