

3894-00

Stainless steel eyewash with bowl, freeze resistant

Krusman eye/facewash for outside use with stainless steel pipes and green/white stripe. Self-draining eye/facewash with built-in flow control and filter for each individual spray head. Stay-open ball valve, operated by a pull handle. Designed for a minimum flow of 28 l/min at 2.4 bar pressure. Freeze resistant and manufactured for Ex-classified environments. The model is available for Ex-classified or non Ex-classified environments.

Emergency signs are enclosed with each eyewash.

TECHNICAL DATA

The shower is constructed for outdoor installation. It is insulated and heat traced in order to prevent freezing. The material is approved for installation in hazard environments.

Water pressure: Automatic function for pressure between 2.4-6.5 bar with built-in flow controls and filters. If the water pressure exceeds 6.5 bar a pressure reducing valve must be installed.

Material: Valves and pull handle are manufactured in stainless steel. Stainless steel pipes and fittings. The spray heads are manufactured in polypropylene plastic.

Trace heated: Self-regulating heating-cable, 4 m (10W/m).

Insulation: Waterbased foam insulation.

Surface: Black PEH plastic pipes. Meet DIN and ISO standards.

Water supply standard: 1" male.

Options: Flange connection, alarm, strobe light, foot pedal, thermostat heating cable, stainless steel.

TECHNICAL INFORMATION

Flow rate: 28 L/min	Width: 350 mm
Water supply: 1" male	Height: 1100 mm
	Depth: 650 mm

