



Product picture note

The tank shower on the picture includes optional fittings such as eyewash, step-on foot grid, back/side panels, signal horn and flashing light.

Manufactured in accordance to ANSI Norm Z358.1- latest edition and SS-EN 15154-1 & 2:latest edition.

7021-00

Stainless steel tank shower with over head tank, 1400L

Insulated and gravity-fed emergency tank shower with a flush time of +15 minutes at a guaranteed flow of 76 L/min. Suitable in areas where there is no main water supply. Emergency shower is operated by a pull handle. Eyewash (optional fitting) is operated by a push plate. Model also available with explosion-proof instrumentation for EX-Zone 1 & 2 (Model 7021-00 EX). Tank shower with chiller see model 7011-00.

TECHNICAL DATA

Flow rate emergency shower:	76 L/min
Water inlet:	1" male, self-closing floating valve (stainless steel 304)
Water overflow:	Pipe thread external 1"
Supply pressure:	0.5 to 10 BAR G
Water level indicator:	Visual pointing outside tank (stainless steel with color indicator)
Thermometer gauge:	Size 100 mm
Insulation tank:	Rockwool insulation 45mm (Thermal conductivity: $\lambda = 37 \text{ mW/mK}$)
Activation time:	Less than 1 second
Identification:	Green/white stripes with emergency pictogram sign
Lifting lugs:	Included

MATERIAL DESCRIPTIONS

Frame:	Stainless steel 316 L
Tank:	Stainless steel 316 L
Pipe work:	Stainless steel 316 L
Valves:	Stainless steel 316 L
Shower head:	Stainless steel 316 L powder coated yellow
Eyewash bowl:	Stainless steel 316 L powder coated yellow (eyewash: optional fitting)
Eyewash heads:	ABS plastic with lids (eyewash: optional fitting)
Pull rod:	Stainless steel 316 L with triangle handle and flag
Nuts, bolts and fixings:	Stainless steel A4

OPTIONAL FITTINGS

Eyewash (model 3863-00 Tank /3868-00 Tank), step-on foot grid, panic-bar, heating element, inductive sensors, flashing light, anti-bacterial fluid, back/side panels, sun shade, catchment (catchment drain: 2" hose connector) and undertank lightning.

DIMENSIONS AND TANK SHOWER DETAILS

Model no.:	7021-00	Width:	1344 mm (measured at top)
Tank size:	1400L	Height:	3621 mm
Weight:	330 kg	Depth:	1226 mm

(weight is without optional fittings and water)